

1204 KSS 夹线套 WIRE SADDLE




无卤素 环保

单位：mm



型 号 Item No.	H1	H2	适用PC板		包 装 Packing
			钻孔 M1	板厚 T1	
LWS-5	7.8	5.4	4.0	2.4	100pcs

材质：UL合格之NYLON 66 (本色)，防火等级 94V-2。




1205 KSS 夹入式扭线环 CLIP TWIST TIE




无卤素 环保

单位：mm



型 号 Item No.	尺 寸 Dimension			包 装 Packing
	W1	H1	H2	
CTT-17	16.7	4.2	30.5	100pcs

材质：UL合格之NYLON 66 (本色)，防火等级 94V-2。




1205 KSS 隔离扭线环 STANDOFF TWIST TIE



无卤素 环保


单位：mm




型 号 Item No.	尺 寸 Dimension			基板孔径 M1	适用板厚 T1	包 装 Packing
	W1	H1	H2			
ST-1	6.0	31.7	19.5	4.6~4.8	1.0~2.8	100pcs
ST-2	11.0	21.2	27.8	4.8~5.0	1.0~2.8	
ST-3	10.4	4.7	27.3	4.6~4.8	1.0~2.8	
ST-3B	11.0	5.0	28.0	6.2~6.6	0.5~2.0	
ST-3C	15.0	5.0	32.0	4.6~4.8	0.5~1.6	
ST-3D	18.0	5.3	36.2	4.4~4.8	1.0~2.4	
ST-4S	11.0	13.0	27.9	4.2~4.8	1.0~2.4	
ST-4	15.0	13.1	31.3	4.6~4.8	1.0~2.0	
ST-0560	5.0	60.9	20.5	4.6~5.0	1.6~3.0	
ST-0605	6.1	5.3	19.3	4.0~4.4	2.4	
ST-0701	7.0	1.3	22.0	4.6~4.8	1.0~2.8	
ST-1112	11.0	15.3	26.8	4.6~4.8	1.6~3.0	
ST-1247	11.0	50.5	27.2	4.6~4.8	1.6~3.0	
ST-1303	13.5	3.0	45.0	6.6	1.8~3.6	
ST-1602	16.0	5.1	31.7	4.4~4.6	0.5~1.6	
ST-2005	20.0	5.1	36.5	7.2~7.6	1.8~3.6	
ST-2403	23.5	3.2	44.2	4.8~5.0	0.5~2.6	

材质：UL合格之 NYLON 66 (本色)，防火等级 94V-2。


用法：使用选定适当的距离钻孔，然后将扭线环固定，再将电线置于环中做正向扭转即可，拆卸时反向扭转即可。




标准设计




ST-3C




ST-3D




ST-4S




ST-0605




ST-0701




ST-1112,1247



ST-1303



ST-2005



ST-2403