



配线槽

配线标志

扎线带

结束带

固定座

固定头、浪管

保护部品

接线头

套管

固定夹

PC板部品

扣具

1215 KSS 粘贴式扭线环 MOUNTING TWIST TIE




单位: mm



型号 Item No.	W	W1	H	束线范围 Bundle Diameter	包装 Packing
TTB-08	17.4	7.9	27.5	7~10	100pcs
TTB-15	22.0	14.8	35.2	10~15	
TTB-20	25.5	20.6	40.0	15~20	

材质: UL合格之NYLON 66 (本色), 防火等级94V-2, 底座背胶。

特点: 1. 粘贴式设计, 可省去面板钻孔之麻烦。
2. 束线简易、牢固, 并可松开, 多次重复使用。

1216 KSS 粘贴式扣线套 ADHESIVE WIRE SADDLE




单位: mm




型号 Item No.	L	W	W1	H2	包装 Packing
AWS-11	19.8	20.0	11.2	11.0	100pcs
AWS-9R	16.0	29.8	8.5	13.6	
AWS-1210	18.3	20.7	11.3	10.0	
AWS-0912	9.5	15.8	9.0	11.6	


材质: UL合格之NYLON 66 (本色), 防火等级94V-2, 底座背胶。




AWS-11



AWS-9R



AWS-1210



AWS-0912

1217 KSS 高压隔离线圈 SPACERS RING




单位: mm




型号 Item No.	H1	H2	O.D.	包装 Packing
SPR-8V0	14.2		28.0	100pcs
SPR-45V0	26.3	22	49.2	

材质: UL合格之 NYLON 66 (白色), 防火等级 94V-0。



SPR-8V0



SPR-45V0