


## 1308 KSS 圆体垫片 ROUND WASHER



无卤素 环保

单位: mm



| 型 号<br>Item No. | H   | H1  | O.D. | I.D. | I.D.1 | 包 装<br>Packing |
|-----------------|-----|-----|------|------|-------|----------------|
| RW-45           | 4.5 | 3.1 | 8.0  | 4.0  | 6.5   | 100pcs         |


材质: UL合格之 NYLON 66 (本色), 防火等级 94V-2。

## 1308 KSS 圆锥体垫片 CONOID WASHER



无卤素 环保

单位: mm



| 型 号<br>Item No. | H    | H1   | O.D. | I.D. | I.D.1 | I.D.2 | 包 装<br>Packing |
|-----------------|------|------|------|------|-------|-------|----------------|
| CDW-12          | 12.2 | 10.7 | 10   | 3.3  | 8.3   | 6.9   | 100pcs         |


材质: UL合格之 NYLON 66 (本色), 防火等级 94V-2。

## 1310 KSS 电晶体垫片 TRANSISTOR WASHER



无卤素 环保

单位: mm



| 型 号<br>Item No. | H   | H1  | O.D. | O.D.1 | I.D. | 包 装<br>Packing |
|-----------------|-----|-----|------|-------|------|----------------|
| TW-63A          | 0.5 | 8.1 | 6.0  | 3.5   | 2.8  | 100pcs         |
| TW-63B          | 1.2 | 1.4 | 6.0  | 3.5   | 2.9  |                |
| TW-63C          | 1.7 | 2.3 | 6.0  | 3.5   | 2.9  |                |
| TW-63D          | 1.9 | 3.2 | 6.0  | 3.5   | 2.9  |                |
| TW-63E          | 2.0 | 2.6 | 6.1  | 3.5   | 2.9  |                |
| TW-63F          | 1.3 | 2.0 | 6.3  | 3.4   | 2.9  |                |
| TW-73A          | 3.0 | 1.8 | 6.6  | 4.2   | 3.2  |                |
| TW-73B          | 1.3 | 2.5 | 6.9  | 3.6   | 2.9  |                |
| TW-83A          | 1.3 | 3.7 | 7.7  | 5.8   | 3.1  |                |
| TW-83B          | 1.2 | 5.6 | 7.8  | 3.6   | 2.9  |                |
| TW-83C          | 2.0 | 0.9 | 7.8  | 4.3   | 3.2  |                |
| TW-83D          | 1.3 | 2.3 | 8.0  | 3.5   | 2.9  |                |
| TW-83E          | 3.7 | 1.2 | 7.8  | 5.9   | 3.2  |                |
| TW-123ABK (黑色)  | 0.5 | 3.0 | 12.0 | 5.9   | 3.2  |                |
| TW-133A         | 1.5 | 1.7 | 12.7 | 7.9   | 3.7  |                |
| TW-163A         | 1.5 | 2.0 | 16.0 | 6.0   | 3.2  |                |
| TW-189A         | 3.3 | 1.5 | 18.0 | 12.4  | 9.3  |                |

材质: UL合格之 NYLON 66 (本色), 防火等级 94V-2。

配线槽

配线标志

扎线带

结束带

固定座

固定头、浪管

保护部品

接线头

套管

固定夹

PC板部品

扣具