


0607 KSS 电缆固定头转接头 GLAND ADAPTOR



材质：UL合格之NYLON66(灰色)，防火等级94V-2。
用途：此产品可将固定头METRIC螺纹转换成PG螺纹。




单位：mm

型 号 Item No.	外螺纹规格 D1				内螺纹规格 D2		宽度 W	包 装 Packing
	螺纹规格 Thread	螺纹外径 Thread O.D.	铁板孔径 Mounting Hole	螺纹长度 L1	螺纹规格 Thread	螺纹长度 L2		
P712GY4	PG7	12.5	12.5+0.2	8	M12X1.5	10	15.0	100pcs
P716GY4	PG7	12.5	12.5+0.2	8	M16X1.5	10	20.0	
P912GY4	PG9	15.2	15.2+0.2	8	M12X1.5	9	18.8	
P916GY4	PG9	15.2	15.2+0.2	8	M16X1.5	10	20.0	
P920GY4	PG9	15.2	15.2+0.2	8	M20X1.5	10	24.0	
P1116GY4	PG11	18.6	18.6+0.2	8	M16X1.5	9	22.0	
P1120GY4	PG11	18.6	18.6+0.2	8	M20X1.5	10	24.0	
P1316GY4	PG13.5	20.4	20.4+0.2	9	M16X1.5	9	24.0	
P1320GY4	PG13.5	20.4	20.4+0.2	9	M20X1.5	10	24.0	
P1325GY4	PG13.5	20.4	20.4+0.2	9	M25X1.5	10	30.0	
P1620GY4	PG16	22.5	22.5+0.2	10	M20X1.5	10	26.8	
P1625GY4	PG16	22.5	22.5+0.2	10	M25X1.5	10	30.0	
P2125GY4	PG21	28.3	28.3+0.3	11	M25X1.5	10	32.5	50pcs
P2132GY4	PG21	28.3	28.3+0.3	11	M32X1.5	12	36.8	
P2932GY4	PG29	37.0	37.0+0.3	11	M32X1.5	10	41.6	
P2940GY4	PG29	37.0	37.0+0.3	11	M40X1.5	11	44.8	25pcs
P3640GY4	PG36	47.0	47.0+0.3	11	M40X1.5	10	55.0	
P4250GY4	PG42	54.0	54.0+0.3	11	M50X1.5	14	55.0	
P4863GY4	PG48	59.3	59.3+0.3	11	M63X1.5	14	68.0	

0607 KSS 电缆固定头转接头 ENLARGER GLAND



材质：UL合格之NYLON66(灰色)，防火等级94V-2。
用途：此产品可将固定头的螺纹外径由大尺寸转换成小尺寸。



单位：mm

型 号 Item No.	外螺纹规格 D1				内螺纹规格 D2		宽度 W	包 装 Packing
	螺纹规格 Thread	螺纹外径 Thread O.D.	铁板孔径 Mounting Hole	螺纹长度 L1	螺纹规格 Thread	螺纹长度 L2		
M1216GY4	M12X1.5	12	12+0.2	8.0	M16X1.5	8.0	20.0	100PCS
M1620GY4	M16X1.5	16	16+0.2	8.0	M20X1.5	10.5	24.0	
M2025GY4	M20X1.5	20	20+0.2	8.0	M25X1.5	10.0	29.0	
M2532GY4	M25X1.5	25	25+0.3	8.0	M32X1.5	11.5	36.0	50PCS
M3240GY4	M32X1.5	32	32+0.3	10.0	M40X1.5	11.5	46.0	25PCS
M4050GY4	M40X1.5	40	40+0.3	10.0	M50X1.5	11.5	55.0	
M5063GY4	M50X1.5	50	50+0.3	10.0	M63X1.5	11.5	68.0	